

<NOTE 1>

Value of C264 is different from kinds of CRT and FBT.

	CRT	510UFB22 -TC52 (DPY)	A48KM12XX44	51GGB95X-TC01
FCM-20B031	0.0027	1.6KV	0.001	1.6KV
154-177T	0.0033	1.6KV	0.0018	1.6KV

<NOTE 2>

1. No Indicated NPN type transistors are used KTC3199 (GR), 2SC1740S (R, S), 2SC3331 (T, U), 2SC1685 (R, S) or 2SC1815 (GR).
2. No Indicated PNP type transistors are used KTA1267 (GR), 2SA933S (R, S), 2SA131B (T, U), 2SA564 (R, S) or 2SA1015 (GR).
3. No Indicated diodes are used 1SS133 or 1SS176.

CAUTION:


FOR CONTINUED PROTECTION AGAINST FIRE HAZARD,

REPLACE ONLY WITH THE SAME TYPE T4AH 250V FUSE.

ATTENTION: POUR UNE PROTECTION CONTINUE LES RISQUES

D'INCENDIE N'UTILISER QUE DES FUSIBLE DE MEMO TYPE T4AH 250V.

RISK OF FIRE - REPLACE FUSE AS MARKED.



TELETEXT SCHEMATIC DIAGRAM

